

# LIFECOAT

Interior Emulsion



## PRODUCT DESCRIPTION

LifeCoat Interior Emulsion adds elegance to your interior walls. This water-based interior paint offers better coverage and durability than distemper. LifeCoat is an excellent choice of paint with its affordability and a superior quality.



## PRODUCT FEATURES



### SMOOTH FINISH

The smooth finish adds elegance to your interior walls

### FINISH

SMOOTH AND MATT

### TOXICITY



- Eco-friendly product with no added lead, mercury and chromium
- Low VOC

### COVERAGE (APPROX)



75-85 sq.ft./L/2 coats

- Coverage may depend on factors like surface conditions, surface preparations, application skills, weather conditions, dilution, etc.
- Coverage for darker shades may vary

## AVAILABLE PACKS



20 ltr



10 ltr



4 ltr



1 ltr

A PRODUCT FROM



**SHYAM STEEL**

SINCE 1953

# LIFECOAT

Interior Emulsion



## DIRECTIONS FOR APPLICATION

### Application Method



Roller/Brush/Spray

### Dilution Ratio



Add 300-400ml of potable water/L of emulsion.  
In case of dark bases, dilute as per requirement

### Recommended Undercoat



Flexi Strong Acrylic Wall Putty  
and  
Dura Fill Interior Primer

### Drying Time



**Surface Dry:** 15-25 minutes

**Hard Dry:** 4-6 Hours

\*Drying time may vary as per weather conditions

## SURFACE PREPARATION AND APPLICATION



- Before application ensure the surface is free from loose particles and dirt
- Wipe clean with a dry cloth and ensure the surface is completely dry
- Apply Dura Fill Interior Primer on the surface, and allow minimum 4 hours drying time
- Apply Flexi Strong Acrylic Wall Putty to cover hairline cracks and uneven surfaces; allow it to dry completely
- Sand the surfaces with sandpaper no. 220 for smoothening, apply another coat of primer; allow sufficient drying time
- Apply 2-3 coats of LifeCoat Interior Emulsion for best results. Keep 4-6 hours of drying time between coats

## IMPORTANT NOTES



- Prior to use, shake the container well
- Dilute the paint to the standard dilution up to 30-40 % by volume. For deeper shade, dilute as per requirement
- After tinting the product with Macaw colour tinting machine, mix properly in gyro shaker
- Do not apply the paint, if the temperature is below 10°C or above 45°C
- Ideal moisture content of wall should be below 12%
- The pH value of the wall must be between 7-11
- Avoid leaving the diluted emulsion exposed for a long time
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

\*T&C apply

### SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-1D, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

