

AMENDO

Red Oxide
Metal Primer



PRODUCT DESCRIPTION

Amendo Red Oxide Metal Primer is a solvent-based product designed to prevent rust formation and to be used on ferrous metal surfaces for protection from corrosion before enamel application.

PRODUCT FEATURES



RUST PROTECTIVE

The primer is a rust inhibitor coating and provides protection from rust



FLAMMABLE LIQUID

This product is flammable in nature and needs to be handled carefully

RECOMMENDED SURFACE



Ferrous Metal Surfaces

AVAILABLE PACKS



10 ltr



4 ltr



1 ltr



500ml

A PRODUCT FROM



SHYAM STEEL

SINCE 1953

AMENDO

Red Oxide Metal Primer



TECHNICAL DATA

Product Type	Primer
Finish	Matt
Consistency	Free-flowing, smooth and uniform
Thinner	MTO
Method of Application	Brush or spray
Recommended Application Viscosity (30°C/FCB4)	Spraying 40-45 sec
Coverage	90-100 sq.ft./L/coat (25 µ DFT)
Drying Time (20°C-30°C and 60+/- 5 RH)	Surface Dry: < 1 hour (at 18-25 µ DFT) Hard Dry: < 24 hours
Re-coating Period	8-10 hours Depends on surface and weather conditions
Flash Point	Above 30°C (Abel closed cup)
Fire Hazard Class	Flammable liquid
Storage	Store in a cool and dry place
Disposal	Dispose as per local regulations. Avoid pouring down the drain
Colour	Red Oxide

SURFACE PREPARATION



- Prior to application of Amendo Red Oxide Metal Primer, ensure the surface is clean and there is no rust
- If required, use MTO for dilution up to 10-15% by volume
- Before paint application, apply 2 coats of Amendo Red Oxide Metal Primer
- Leave it to dry for approximately 6-8 hours in normal weather conditions before application of subsequent coats
- The metal primer can be applied by brush or spray

IMPORTANT NOTES



- Shake the container and stir well before use; do not over dilute
- Store safely and away from flammable source
- Keep the container tightly closed after use
- Keep out of reach of children. In case of direct eye contact, rinse thoroughly with clean water and seek medical help, if required
- Store away from edibles

SAFETY & CAUTION

- During application and drying of the primer, ensure good ventilation
- Put on protective clothes, gloves, eye protector and nose pad while painting and rubbing the surface
- Smoking while painting is strictly prohibited
- Do not inhale the vapour

LEAD CONTENT DOES NOT EXCEED 90 PARTS PER MILLION

*T&C apply

SSIL Paint Industries Pvt. Ltd.

Premises No. 03-319, DH-6/11, Street No. 319, Action Area-1D, North 24 Parganas, New Town, Kolkata-700156, West Bengal

For feedback/complaints, write to the customer care at the above address or call

☎: 1800 309 4007 | ✉: enquiry@macawpaints.com | 🌐: www.macawpaints.com

A PRODUCT FROM

